

TR-CONTROL

Addressable Notification Module

GENERAL

The TR-CONTROL is an addressable notification module for use with Triga Series fire alarm control panels (FACPs). The TR-CONTROL gives you the flexibility to add notification circuits wherever they are needed on a Triga FACP signaling line circuit (SLC) loop.

The TR-CONTROL provides supervised monitoring of wiring to load devices that require an external power supply to operate, such as bells, horns, and strobes. It is capable of Class B and Class A supervision.

Upon command from the FACP, the TR-CONTROL will disconnect the supervision and connect the external power supply across the load device. The disconnection of the supervision provides a positive indication to the panel that the control relay actually turned on. The external power supply is always relay isolated from the SLC loop, so that a trouble condition on the power supply will never interfere with the rest of the system.

INSTALLATION

The TR-CONTROL mounts directly into a 4" square electrical box. The box must have a minimum depth of 2-1/8". A surface mount electrical box (TR-SMB500) is available from Triga.

COMPATIBILITY

The TR-CONTROL is compatible with the following Triga Series FACPs:

- TR-2100R / TR-2100B
- TR-2100ECSR / TR-2100ECSB
- TR-R2100R / TR-R2100B



TR-Control Module

FEATURES & BENEFITS

- Flexible solution for adding notification circuits where needed
- Support for Class B (style Y) or Class A (style Z) wiring
- Panel controlled status LED that flashes green in normal state and is solid red in alarm
- Polling LED visible through the cover plate
- Rotary address switches for fast installation
- SEMS screws for easy wiring
- UL Listed
- FM Approved



Technical Specifications

PHYSICAL

Dimensions: 4.5" H x 4"W x 1.25" D

Shipping Weight: 6.3oz (196g)

ENVIRONMENTAL

Operating Temperature: 32°F to 120°F (0°C to 49°C)

Humidity: 10% to 93% relative humidity
(noncondensing)

ELECTRICAL

Operating Voltage: 15 to 32VDC

Standby & Alarm Current: 350 mA

End-of-Line Resistance: 47k

SLC Loop Impedance: 40

ACCESSORIES

TR-SMB500: 4" Square Surface Mount Electrical Box

TR-CB500: Module Barrier. Used to separate power limited and non-power limited wiring in a junction box

AGENCY LISTINGS

NFPA 13, NFPA 70, NFPA 72, UL 2572, UL 1711 &

UL 864: Local Protective Signaling Systems

UL Listed

This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.

TRIGA Life Safety Systems, LLC
7600 Olde Eight Rd, Hudson, Ohio, United States of America
Tel : +1 330-577-5199, Email: info@trigaglobal.com